


RC

 Round **Positive**
Relief Angle: 7°



Dimensions (mm)			
Size	d	t	d ₁
06	6.0	2.38	2.8
08	8.0	3.18	3.35
10	10.0	3.18~3.97	4.4
12	12.0	4.76	4.4

Workpiece	Steel	P						Machining types
	Stainless steel	M						
	Cast iron	K						
	Non-ferrous metal	N	*	●	*	●	*	
	Heat resistant alloy, Titanium alloy	S						
	Hardened steel	H						
● Continuous cutting ● General cutting * Interrupted cutting								

Inserts	Designation	Coated			Uncoated		Cutting Condition	
		PC5040	PD1000	PD1010	H01	H05	f _n (mm/rev)	a _p (mm)
AK 	RCGT 0602M0-AK				●	●	0.05~0.20	0.50~2.00
	0803M0-AK				●	●	0.05~0.25	0.50~2.50
	1003M0-AK				●	●	0.10~0.30	1.00~3.00
	10T3M0-AK						0.10~0.30	1.00~3.00
	1204M0-AK				●	●	0.10~0.35	1.00~3.50
AR 	RCGT 0602M0-AR						0.05~0.20	0.50~2.00
	0803M0-AR						0.05~0.25	0.50~2.50
	1003M0-AR				●	●	0.10~0.30	1.00~3.00
	10T3M0-AR						0.10~0.30	1.00~3.00
	1204M0-AR						0.10~0.35	1.00~3.50

 Cutting edge geometry **A52~A61**
 Recommended chip breaker **B04~B11**
 Code system **B26~B27**
● : Stock item

Available tool holders			
Designation	Page	Designation	Page
SRDCN	B179	SRGCR/L	B180