

FMAC(M)3000-A

Aluminum body





Fig. 1




Fig. 2



AA
45°






• AR: 21°
• RR: -16°~ -12°

(mm)

Designation			ØD	ØD2	Ød	a	b	E	F	Ød1	Ød2	ap	 kg	Fig.
FMACM	3063R-A	3	63	49	22	10.4	6.3	20	40	11	18	4	0.5	1
FMAC (FMACM)	3080R-A	4	80	57	25.4 (27)	9.5 (12.4)	6 (7)	25	50	13.5	20	4	0.6	1
	3100R-A	5	100	67	31.75 (32)	12.7 (14.4)	8 (8)	32	50	-	45	4	0.8	2
	3100R-25.4-A	5	100	67	25.4	9.5	6	25	50	-	38	4	0.9	2
	3125R-A	6	125	87	38.1 (40)	15.9 (16.4)	10 (9)	38	63	-	56	4	1.6	2
	3125R-25.4-A	6	125	70	25.4	9.5	6	25	63	-	38	4	1.7	2

() Metric size

Available inserts

		SEET-MF		SEET-MM		SEET-MA		SEXT-MF		SEXT-MM		SEXT-MR		SEEW							
																					
Designation		Cermet		Coated										Uncoated				page			
		CN2000	CN30	NCM325	NC5330	NCM535	NCM545	PC2505	PC2010	PC3600	PC3700	PC6510	PC9530	PC9540	PC5300	PC5400	ST30A			G10	H01
SEET	0903AGFN-MA																		●	●	E19 E20
	0903AGSN-MF										●	●			●	●					
	0903AGSN-MM			●								●				●	●				
SEXT	0903AGSN-MF									●		●			●	●					
	0903AGSN-MM									●	●	●			●	●					
	0903AGSN-MR																				
SEEW	0903AGTN																				

Available arbors

Designation	Ød	NC arbors
FMACM 3063R-□	22	BT□□-FMC22-□□
FMAC 3080R-□	25.4	BT□□-FMA25.4-□□
	27	BT□□-FMC27-□□
3100R-□	31.75	BT□□-FMA31.75-□□
	32	BT□□-FMC32-□□
3125R-□	38.1	BT□□-FMA38.1-□□
	40	BT□□-FMB40-□□

Parts

Specification					
Ø63~Ø125	FTKA0307	TW09S	HW30L	LFMA3R-A	DHA620

Available inserts E19, E20 Available arbors and bolt E400~E402

