



FMPC(M)4000


AA
90°


- AR: 10°
- RR: -9° ~ -8°

(mm)

Designation			ØD	ØD ₂	Ød	a	b	E	F	Ød ₁	Ød ₂	ap	
FMPCM	4063HS	5	63	49	22	10.4	6.3	20 (20)	50 (50)	11	18	11	0.4
FMPC (FMPCM)	4080HS	6	80	57	25.4 (27)	9.5 (12.4)	6 (7)	25 (23)	50 (50)	14	20	11	0.9
	4100HS	7	100	67	31.75 (32)	12.7 (14.4)	8 (8)	33 (25)	63 (50)	18	26	11	1.9 (1.5)
	4125HS	8	125	87	38.1 (40)	15.9 (16.4)	10 (9)	35 (29)	63	22	32	11	3.1

() Metric size

Available inserts

		SDET-MF		SDET-MM		SDET-MA		SDXT-MF		SDXT-MM		SDXT-MA									
																					
Designation		Cermet		Coated										Uncoated				page			
		CN2000	CN30	NCM325	NCM335	NC5330	NCM535	NCM545	PC3600	PC3700	PC6510	PC9530	PC9540	PC5300	PC5400	PD1010	ST30A		G10	H01	H05
SDET	130504R-MA														●				●	●	E17
	130508R-MF																				
	130508R-MM																				
SDXT	130508R-MF			●					●		●	●		●	●						E18
	130508R-MM			●	●				●	●	●	●		●	●						
	130508R-MA																		●	●	


Available arbors

Designation	Ød	NC arbors
FMPCM 4063HS	22	BT□□-FMC22-□□
FMPC 4080HS	25.4	BT□□-FMA25.4-□□
(FMPCM)	27	BT□□-FMC27-□□
4100HS	31.75	BT□□-FMA31.75-□□
	32	BT□□-FMC32-□□
4125HS	38.1	BT□□-FMA38.1-□□
	40	BT□□-FMB/FMC40-□□

Parts

Specification		
		
Ø63-Ø125	FTNC04511	TW20S

Assembling



Available inserts E17,E18 Available arbors and bolt E400~E402