


RM3PC(M)5000 new



AA
90°
• AR: -5°
• RR: -7°

Designation			ØD	ØD2	Ød	Ød1	Ød2	Ød3	a	b	E	F	ap	
RM3PC (RM3PCM)	5080HR	5	80	57	25.4 (27)	14	20	35	9.5 (12.4)	6 (7)	24 (23)	50	12.0	0.84
	5080HR-M	7	80	57	25.4 (27)	14	20	35	9.5 (12.4)	6 (7)	24 (23)	50	12.0	0.84
	5100HR	7	100	67	31.75 (32)	18	28	45	12.7 (14.4)	8 (8)	32 (25)	63	12.0	1.76
	5100HR-M	8	100	67	31.75 (32)	18	28	45	12.7 (14.4)	8 (8)	32 (25)	63	12.0	1.76
	5125HR	8	125	90	38.1 (40)	22	32	52	15.9 (16.4)	9 (10)	38 (30)	63	12.0	2.70
	5125HR-M	10	125	90	38.1 (40)	22	32	52	15.9 (16.4)	9 (10)	38 (30)	63	12.0	2.70

() Metric size

Available inserts



Designation		Cermet		Coated											Uncoated			page		
		CN2000	CN30	NCM325	NC5330	NCM535	NCM545	PC2505	PC2510	PC3600	PC3700	PC6510	PC9530	PC9540	PC5300	PC5400	ST30A		G10	H01
XNCT	120608PNFR-MA																		●	E29 E30
XNKT	120604PNSR-MM													●	●					
	120608PNER-ML									●		●		●	●					
	120608PNSR-MM						●	●	●		●		●	●	●					
	120612PNER-ML													●	●					
	120612PNSR-MM						●	●						●	●					
	120616PNER-ML													●	●					
	120616PNSR-MM						●	●						●	●					
	120620PNER-ML													●	●					
	120620PNSR-MM						●	●						●	●					

Available arbors

Designation		Available arbors	
		RM3PC	RM3PCM
RM3PC(M)	5080HR	BT□□-FMA25.4-□□	BT□□-FMC27-□□
	5100HR	BT□□-FMA31.75-□□	BT□□-FMC32-□□
	5125HR	BT□□-FMA38.1-□□	BT□□-FMC40-□□

Parts

Specification		
Ø80~Ø125	FTNA0511	TW20-100

Available inserts E29, E30 Available arbors and bolt E400~E402